

# BINDER S 205

Acrylic Binder



## Chemical Composition

**Binder S 205** is partially self-crosslinking acrylic copolymer that would provide good covering to poor grain leather.

**Binder S 205** has good toluene and water resistant properties.

## Application

- A. Full grain nappa leather
- B. Full and corrected grain upholstery leather
- C. Split finishing
- D. Corrected grain shoe upper
- E. **Wax H** can be used to control tackiness
- F. White and pastel color leather
- G. Due to its self-thickening properties, **Binder S 205** should be added last in the finishing mixture

## Properties

Appearance:	Milky White Liquid
Analysis:	pH 2.5-5.0
Active Ingredient:	17-19%
Density:	1.00-1.10 KG/L.
Storage Condition:	Optimum Condition is between +5C and +30C. Keep away from below freezing temperature. Keep in cool and well ventilated warehouse.
Shelf Life:	Up to 12 months in the original packing condition.

## Packing

120KGS Plastic Drums

The information and technical advice are provided to you 'as is' and the Company expressly disclaims all warranties of any kind, either implied or expressed. You agree to indemnify and hold harmless the Company and its representatives, subsidiaries, affiliates, related parties, officers, directors, employees, agents from any claim or demand, including reasonable legal fees, that may be filed by any third party, arising out of your conduct or connection with the use of "Product Literature" or "Technical Information" or "Technical Advice" or "Technical Guidance" or any "Recommendation".

Written on 25 August 2016

Product Literature

Page 103 of 129

ALLIED CHEMICALS INTERNATIONAL CO., LTD.: 255/2 Bangpoo Industrial Estate Soi 3, Praekasa, Amphur Muang, Samutprakarn 10280 ■ THAILAND  
Tel: (662) 7094125 ■ Fax: (662) 323-1626-7 [info@acicth.com](mailto:info@acicth.com) <http://www.allied-chemical.co.th>